



Room 2303, Office Tower, Convention Plaza  
1 Harbour Road, Wanchai, Hong Kong  
Tel. +852 2860 0049 - Fax +852 2873 9094  
e-mail: info@maxiledscreens.com

## INDUSTRIAL COMPUTER



### **LED-6488** industrial computer configuration:

System: support WIN98/WIN2000/WIN XP / WINCE / XPE / Linux

Chassis: silver white dust aluminum alloy chassis (on both sides of a dust sponge)

Embedded computer motherboards: VIA C3 - 1G embedded motherboard for low power consumption (with CE, FCC, MBTF testing), integrated 2D/3D S3 graphics, MPEG-4 hardware decompression.

Memory: 1 DDR266 DIMM slots, the maximum support 1G

Storage devices: internal 2.5 "HDD Drive Bay × 1, Low Power Design Earthquake

Expansion slots: a 32 - bit PCI expansion slots

LVDS: LVDS interface card can be sent directly linked with (a line connecting plate marked IPC lateral side and sent cards, to pay special attention to marking and inserted methods)

BIOS: Award BIOS 2/4M flash (in the BIOS POWER MANGE calls can be set up boot)

Dimensions: 410mm × 210mm × 60mm

LED instructions: a power switch indicator, a hard disk indicator visit

Power supply: a power input range: 100 to 240Vdc

Power output: +5 V; +12 V; - 12V; +3.3 V; +5 VSB; GND; PS ON #; POWER OK

Room 2303, Office Tower, Convention Plaza  
1 Harbour Road, Wanchai, Hong Kong  
Tel. +852 2860 0049 - Fax +852 2873 9094  
e-mail: info@maxiledscreens.com

[page 2 of 2](#)

Power Line: ATX connector

Rated power: 200 W

Certification: CE, FCC, CCC

Input / output:

VGA interface x 1, PS / 2 keyboard / mouse interface x 1, Serial x 1, RJ45 x 2, LPT x 1,  
AUDIO.

USB 4 x USB

Ethernet two 10/100 Fast Ethernet mouth

Environment

Operating temperature 0 ° C to 60 ° C

Storage temperature -20 ° C to 80 ° C

Relative humidity 10% to 90%



**ASIA MANUFACTURES GROUP LTD**

Room 2303, Office Tower, Convention Plaza - 1 Harbour Road, Wanchai, Hong Kong

Tel. +852 2860 0049 - Fax +852 2873 9094 - email: info@maxiledscreens.com